

LED-Dimmer

LED dimmer, rotary 2-100VA, with neon lamp, Jussi

Type: 6523URJGL-214-103

GTIN: 4011395232118

Optimized for dimming of Philips retrofit LEDs (LEDi). With rotary control, soft-catch and with leading edge control.

For incandescent lamps, 230V tungsten halogen lamps and low-voltage halogen lamps with conventional transformers or electronic (LC) transformers and dimmable halogen energy-saving lamps.

Mix operaton of LEDi with conventional loads possible.

Low-noise level by MOSFET transistors.

With electronic short-circuit protection.

With electronic overload protection.

With adjustable minimum brightness.

Product includes insert, center plate and frame.

Note!

There might be limitations from transformer producers on how many dimmable LED bulbs can be connected behind one transformer

Technical specification

General Information

| Product ID: | 2CKA006512A0346 | |
|-------------|-----------------|--|
| Packing | | |
| Package: | 1/10 | |
| Unit: | PCS | |

ETIM Data

| Assembly arrangement: | Basic element with central cover plate |
|-----------------------|--|
| | |

© ABB 2024

Business ID 0763403-0

Customer service

puh. +358 10 222 1999 contact.center@fi.abb.com ABB Exchange

+358 10 22 11



Product Card

LED dimmer, rotary 2-100VA, with neon lamp, Jussi



| Method of operation: | Turn/push button |
|--|------------------------------|
| Type of load: | Universal and LED Retrofit |
| Minimum brightness controllable: | Yes |
| Mounting method: | Flush mounted (plaster) |
| Type of fastening: | Mounting with claw and screw |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | No |
| Surface protection: | Untreated |
| Surface finishing: | Glossy |
| Colour: | White |
| RAL-number (similar): | 9010 |
| Suitable for degree of protection (IP): | IP21 |
| Impact strength: | IK00 |
| Nominal voltage: | 207253 V |
| Frequency: | 5060 Hz |
| Control voltage: | 220240 V |
| Connection type: | Screwed terminal |
| Core cross section: | 1.02.5 mm² |
| Device width: | 85 mm |
| Device height: | 85 mm |
| Device depth: | 44 mm |
| Min. depth of built-in installation box: | 20 mm |
| Compatible with Apple HomeKit: | No |
| Compatible with Google Assistant: | No |
| Compatible with Amazon Alexa: | No |
| IFTTT support available: | No |
| | |