


Dimmer

Cover Plates (partly incl. Insert) white - Saga



Type: 6523 UC-916-510

GTIN: 4011395316375

Very small installation depth: < 20 mm Without claws. With rotary control, two-way switch and soft-catch. 2-wire connection (neutral conductor not required) Optimised for dimming of retrofit LED lamps (LEDi). For dimmable Retrofit-LEDs (LEDi). For dimmable Retrofit-LEDs (LEDi) with conventional or electronic transformers. For incandescent lamps, 230 V tungsten halogen lamps, low-voltage halogen lamps with conventional or electronic transformers and dimmable energy-saving halogen lamps. Mix operaton of LEDi with conventional loads possible. With manually adjustable operating mode: trailing / leading edge control. With adjustable minimum/maximum brightness. Low-noise level by MOSFET transistors. With electronic short-circuit protection. With electronic overload protection. Rated voltage: 230 V~, + 10% / - 10% Rated frequency: 50 Hz/60 Hz Nominal power: 2 - 100 W/VA (leading edge control) Nominal power: 2 - 400 W/VA (trailing edge control)

Technical specification

General Information

| | |
|-------------|-----------------|
| Product ID: | 2CKA006512A0352 |
|-------------|-----------------|

Packing

| | |
|----------|-----|
| Package: | 1/1 |
| Unit: | PCS |

ETIM Data

| | |
|-----------------------|--|
| Assembly arrangement: | Basic element with central cover plate |
|-----------------------|--|

Product Card

Cover Plates (partly incl. Insert) white - Saga



| | |
|---|------------------------------|
| Method of operation: | Turn/push button |
| App control via Bluetooth: | No |
| Dimming phase cut-on: | Yes |
| Dimming phase cut-off: | Yes |
| Serial dimmer: | No |
| Type of load: | Universal and LED Retrofit |
| Substation input: | Yes |
| Light value memory: | Yes |
| Applicable with button: | Yes |
| Applicable with movement sensor: | No |
| Applicable with presence indicator: | No |
| Applicable with time switch/timer: | No |
| Applicable with transmission button: | No |
| Applicable with infrared button: | No |
| Minimum brightness controllable: | Yes |
| Mounting method: | Flush mounted (plaster) |
| Type of fastening: | Mounting with claw and screw |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Yes |
| Surface protection: | Untreated |
| Surface finishing: | Glossy |
| Colour: | White |
| RAL-number (similar): | 9003 |
| Transparent: | No |
| Suitable for degree of protection (IP): | IP21 |
| Impact strength: | IK00 |
| Nominal voltage: | 207...253 V |
| Frequency: | 50...60 Hz |
| Control voltage: | 220...240 V |
| Connection type: | Screw terminal |
| Core cross section: | 1.0...2.5 mm ² |
| Device width: | 71 mm |
| Device height: | 71 mm |

Product Card

Cover Plates (partly incl. Insert) white - Saga



| | |
|--|-------|
| Device depth: | 45 mm |
| Min. depth of built-in installation box: | 20 mm |
| Compatible with Apple HomeKit: | No |
| Compatible with Google Assistant: | No |
| Compatible with Amazon Alexa: | No |
| IFTTT support available: | No |