

## Product Card

Socket residual current device with a rated current of 16 A and s rated residual current of 30mA.



# Fault current pro

Socket residual current device with a rated current of 16 A and s rated residual current of 30mA.


**Type:** 3120EUC-84

**Product ID:** 2CCF019491R0001

**GTIN:** 7612271472283



Socket residual current device with a rated current of 16 A and s rated residual current of 30mA.



## Technical specification

### Electrical quantities

Nominal current:	16 A
Nominal voltage:	230 V

### Classification

Suitable for degree of protection (IP):	IP21
---	------

### Packing

Package:	1/10
Unit:	PCS

### ETIM Data

© ABB 2025

Business ID 0763403-0

[www.installationmaterials.com](http://www.installationmaterials.com)

**Customer service**

puh. +358 10 222 1999

[contact.center@fi.abb.com](mailto:contact.center@fi.abb.com)

**ABB Exchange**

+358 10 22 11

# Product Card

Socket residual current device with a rated current of 16 A and s rated residual current of 30mA.



ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	No
Number of units:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9016
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	Yes
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Glossy
Anti-bacterial treatment:	No
With loop through function:	Yes
With on/off switch:	No

# Product Card

Socket residual current device with a rated current of 16 A and s rated residual current of 30mA.



Rotated central insert:	No
Frequency:	50...60 Hz
Rated fault current:	30 mA
Device width:	71 mm
Device height:	71 mm
Device depth:	56 mm
Min. depth of built-in installation box:	40 mm
Compatible with Apple HomeKit:	No
Compatible with Amazon Alexa:	No
Compatible with Google Assistant:	No
IFTTT support available:	No