

# Fault current protection

Residual current device with a rated current of 16 A and s rated residual current of 30mA.

**Type: 3150UC-84.1** 

Product ID: 2CCF019492R0001

GTIN: 7612271473808








Residual current device with a rated current of 16 A and s rated residual current of 30mA.





# **Technical specification**

#### **Electrical quantities**

Nominal current:	16 A
Nominal voltage:	230 V

#### Classification

|--|

#### **Packing**

Package:	1/10
Unit:	PCS

#### **ETIM Data**

© ABB 2025 **Business ID** 0763403-0 www.installationmaterials.com **Customer service** puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange** 

+358 10 22 11

## **Product Card**

Residual current device with a rated current of 16 A and s rated residual current of 30mA.



ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
With signal lamp:	No
Number of units:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	No
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9016
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	Yes
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Glossy
Anti-bacterial treatment:	No
With loop through function:	Yes
With on/off switch:	No
Rotated central insert:	No

© ABB 2025
Business ID 0763403-0
www.installationmaterials.com

Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange** +358 10 22 11

## **Product Card**

Residual current device with a rated current of 16 A and s rated residual current of 30mA.



Frequency:	5060 Hz
Rated fault current:	30 mA
Device width:	71 mm
Device height:	71 mm
Device depth:	56 mm
Min. depth of built-in installation box:	40 mm
Compatible with Apple HomeKit:	No
Compatible with Amazon Alexa:	No
Compatible with Google Assistant:	No
IFTTT support available:	No

© ABB 2025
Business ID 0763403-0
www.installationmaterials.com

**Customer service** puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange** +358 10 22 11