

Tele outlet

Tele outlet, 22,5mm hole, white matt


Type: 2533-884


Product ID: 2CKA001724A4296

GTIN: 4011395128671



Center plate with a round 22,5mm dented opening that prevents rotation. Used for fastening different devices. It is suitable for the 85mm cover frames. The manufacture material is a durable high quality plastic. The surface is painted. Cleaning with a mild, standard household detergent. Be careful when cleaning with a powerful dissolvent.





Technical specification

Packing

Package:	1/10
Unit:	PCS

ETIM Data

Assembly arrangement:	Control element
Utilization:	Bore hole
Support ring:	Yes
With dust cover:	No
With hinged lid:	No
Outlet direction:	Straight
Imprintable label:	Without indication field

© ABB 2024

Business ID 0763403-0

www.installationmaterials.com

Customer service

puh. +358 10 222 1999 contact.center@fi.abb.com ABB Exchange

Product Card

Tele outlet, 22,5mm hole, white matt



Mounting method: Flush mounted (plaster) Material: Plastic Material quality: Thermoplastic Halogen free: Yes Anti-bacterial treatment: No Surface protection: Lacquered Surface finishing: Matt Colour: White RAL-number (similar): 9016 Transparent: No Type of fastening: Mounting with screw Number of modules (module system): 1 With buses/couplings: No Suitable for number of connectors: 1 With strain relief: No Shelded buses: No Shelded busing: No Stelded housing: No Suitable for degree of protection (IP): P20 Device width: 71 mm Device width: 71 mm Device depth: 17.8 mm Min. depth of built-in installation box: 32 mm	With imprint:	No
Material quality:ThermoplasticHalogen free:YesAnti-bacterial treatment:NoSurface protection:LacqueredSurface finishing:MattColour:WhiteRAL-number (similar):9016Transparent:NoType of fastening:Mounting with screwNumber of modules (module system):1With buses/couplings:NoSuitable for number of connectors:1With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP2ODevice width:71 mmDevice height:71 mmDevice depth:17.8 mm	Mounting method:	Flush mounted (plaster)
Halogen free:YesAnti-bacterial treatment:NoSurface protection:LacqueredSurface finishing:MattColour:WhiteRAL-number (similar):9016Transparent:NoType of fastening:Mounting with screwNumber of modules (module system):1With buses/couplings:NoSuitable for number of connectors:1With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Material:	Plastic
Anti-bacterial treatment:NoSurface protection:LacqueredSurface finishing:MattColour:WhiteRAL-number (similar):9016Transparent:NoType of fastening:Mounting with screwNumber of modules (module system):1With buses/couplings:NoSuitable for number of connectors:1With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Material quality:	Thermoplastic
Surface protection:LacqueredSurface finishing:MattColour:WhiteRAL-number (similar):9016Transparent:NoType of fastening:Mounting with screwNumber of modules (module system):1With buses/couplings:NoSuitable for number of connectors:1With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Halogen free:	Yes
Surface finishing: Matt Colour: White RAL-number (similar): 9016 Transparent: No Type of fastening: Mounting with screw Number of modules (module system): 1 With buses/couplings: No Suitable for number of connectors: 1 With strain relief: No Shielded housing: No Shielded housing: No Suitable for degree of protection (IP): IP20 Device width: 71 mm Device height: 71 mm Device depth: 17.8 mm	Anti-bacterial treatment:	No
Colour:WhiteRAL-number (similar):9016Transparent:NoType of fastening:Mounting with screwNumber of modules (module system):1With buses/couplings:NoSuitable for number of connectors:1With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Surface protection:	Lacquered
RAL-number (similar): 9016 Transparent: No Type of fastening: Mounting with screw Number of modules (module system): 1 With buses/couplings: No Suitable for number of connectors: 1 With strain relief: No Shielded buses: No Shielded housing: No Luster terminal: No With lighting: No Suitable for degree of protection (IP): IP20 Device width: 71 mm Device depth: 17.8 mm	Surface finishing:	Matt
Transparent: No Type of fastening: Mounting with screw Number of modules (module system): 1 With buses/couplings: No Suitable for number of connectors: 1 With strain relief: No Shielded buses: No Shielded housing: No Luster terminal: No With lighting: No Suitable for degree of protection (IP): IP20 Device width: 71 mm Device height: 71 mm Device depth: 17.8 mm	Colour:	White
Type of fastening: Mounting with screw Number of modules (module system): 1 With buses/couplings: No Suitable for number of connectors: 1 With strain relief: No Shielded buses: No Shielded housing: No Luster terminal: No With lighting: No Suitable for degree of protection (IP): IP20 Device width: 71 mm Device height: 71 mm Device depth: 17.8 mm	RAL-number (similar):	9016
Number of modules (module system):1With buses/couplings:NoSuitable for number of connectors:1With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Transparent:	No
With buses/couplings:NoSuitable for number of connectors:1With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Type of fastening:	Mounting with screw
Suitable for number of connectors:1With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Number of modules (module system):	1
With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	With buses/couplings:	No
Shielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Suitable for number of connectors:	1
Shielded housing:NoLuster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	With strain relief:	No
Luster terminal:NoWith lighting:NoSuitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Shielded buses:	No
With lighting: Suitable for degree of protection (IP): Device width: 71 mm Device height: 71 mm 17.8 mm	Shielded housing:	No
Suitable for degree of protection (IP):IP20Device width:71 mmDevice height:71 mmDevice depth:17.8 mm	Luster terminal:	No
Device width: 71 mm Device height: 71 mm Device depth: 17.8 mm	With lighting:	No
Device height: 71 mm Device depth: 17.8 mm	Suitable for degree of protection (IP):	IP20
Device depth: 17.8 mm	Device width:	71 mm
	Device height:	71 mm
Min. depth of built-in installation box: 32 mm	Device depth:	17.8 mm
	Min. depth of built-in installation box:	32 mm