

Product Card

Adapter for DKS-system, fiber 2 x Simplex ST



Adapter

Adapter for DKS-system, fiber 2 x Simplex ST



Type: 1870 EB

Product ID: 2CKA001764A0216

GTIN: 4011395454107



The adapters 18xxEB and the center plates 1758-xx form the DKS-system. You can use the DKS-system to fix many kinds of tele-connectors to Impressivo- or Jussi-series.

Technical specification

Classification

| | |
|---|------|
| Suitable for degree of protection (IP): | IP20 |
|---|------|

Packing

| | |
|----------|--------|
| Package: | 10/100 |
|----------|--------|

| | |
|-------|-----|
| Unit: | PCS |
|-------|-----|

ETIM Data

| | |
|---------------|----------|
| ETIM Version: | ETIM-9.0 |
|---------------|----------|

| | |
|-------------|----------|
| ETIM Class: | EC000018 |
|-------------|----------|

| | |
|-----------------------|-----------------|
| Assembly arrangement: | Control element |
|-----------------------|-----------------|

| | |
|--------------|-------|
| Utilization: | Other |
|--------------|-------|

| | |
|---------------|----|
| Support ring: | No |
|---------------|----|

| | |
|------------------|----|
| With dust cover: | No |
|------------------|----|

Product Card

Adapter for DKS-system, fiber 2 x Simplex ST



| | |
|--|--------------------------|
| With hinged lid: | No |
| Outlet direction: | Inclined |
| Imprintable label: | Without indication field |
| With imprint: | No |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Yes |
| Anti-bacterial treatment: | No |
| Surface protection: | Untreated |
| Surface finishing: | Matt |
| Colour: | Anthracite |
| RAL-number (similar): | 7021 |
| Transparent: | No |
| Number of modules (module system): | 1 |
| With buses/couplings: | No |
| Suitable for number of connectors: | 2 |
| With strain relief: | No |
| Shielded buses: | No |
| Shielded housing: | No |
| Luster terminal: | No |
| With lighting: | No |
| Device width: | 59 mm |
| Device height: | 46 mm |
| Device depth: | 12 mm |
| Min. depth of built-in installation box: | 32 mm |