

---

# Socket outlet


Busch-Protector® Socket insert - Saga

---

**Type:** 2310 EUGL/VAB-916-510

**Product ID:** 2CKA002011A6294

**GTIN:** 4011395316276



Shuttered. With screw-type terminals. DP (2 P + E) With integrated and external signalling contact. Device protection for technical sensitive equipment such as computer, entertainment electronics and building management systems. Effectively reduces overvoltage peaks occurring between the sub-distribution switch board and SCHUKO® socket outlet. Arrestor test class: classification Type 2 ISN = 5 kA

## Technical specification

### Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

### Classification

Suitable for degree of protection (IP):	IP20
---	------

### Packing

Package:	1/1
Unit:	PCS

### ETIM Data

Number of active pins (round):	2
With signal lamp:	No

# Product Card

Busch-Protector® Socket insert - Saga



Number of units:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Screw terminal
With hinged lid:	No
With enhanced contact protection:	No
Label space/information surface:	No
Colour:	Other
RAL-number (similar):	9003
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	Yes
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	Yes
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	No
Surface protection:	Untreated
Surface finishing:	Glossy
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No
Impact strength:	IK03
Device width:	71 mm

# Product Card

Busch-Protector® Socket insert - Saga



Device height:	71 mm
Device depth:	47 mm
Min. depth of built-in installation box:	32 mm
Compatible with Apple HomeKit:	No
Compatible with Amazon Alexa:	No
Compatible with Google Assistant:	No
IFTTT support available:	No