

Socket outlet

Socket outlet, Schuko, 1-gang, shuttered, screwless terminals, LED light, matt white

Type: 20 EUCBLI-884

Product ID: 2CKA002013A5326

GTIN: 4011395129883







There are terminals for each contact of the socket outlet. The terminals are for max 2 solid or rigid wires. No X-terminals. A white color LED light (230V/2,5mA/0,6VA) is integrated into the socket outlet. The light can be controlled seperately or it can be connected to the socket terminals.

Technical specification

Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

Classification

Suitable for degree of protection (IP):	IP20

Packing

Package:	1
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0

© ABB 2025

Business ID 0763403-0 www.installationmaterials.com **Customer service** puh. +358 10 222 1999

contact.center@fi.abb.com

ABB Exchange +358 10 22 11

Product CardSocket outlet, Schuko, 1-gang, shuttered, screwless terminals, LED light, matt white



Number of active pins (round): 2 With signal lamp: No Number of units: 1 Number of phases: 1 Imprint/indication: None With singed lid: No With singed lid: No Unith singed lid: No Unith singed lid: No Lobel space/information surface: No Colour: White RAL-number (similar): 9016 Metallic colour: No Transparent: No Lockable: No Lockable: No With a function lighting: Yes With function lighting: Yes View voltage protection: No View voltage protection: No View voltage protection: No Special power supply: Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastening: Mounting with claw and screw Material: Plastic Material: Plastic <	ETIM Class:	EC000125
Number of phases: 1 Imprint/Indication: None With hinged lid: No With enhanced contact protection: Yes Label space/information surface: No Colour: White RAL-number (similar): 9016 Metallic colour: No Metallic colour: No Lockable: No Eject-mechanism: No Insulated mounting: Yes With function lighting: No With orientation lighting: No Over voltage protection: No Fault current protection: No Special power supply: Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastening: Mounting with claw and screw Material: Plastic Material quality: Thermoplastic Halogen free: Yes Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No Wi	Number of active pins (round):	2
Number of phases: 1 Imprint/indication: None With hinged lid: No With enhanced contact protection: Yes Label space/information surface: No Colour: White RAL-number (similar): 9016 Metallic colour: No Metallic colour: No Insuparent: No Lockable: No Eject-mechanism: No Insulated mounting: Yes With function lighting: No With orientation lighting: No Over voltage protection: No Vers No Over voltage protection: No With miniature fuse: No Over voltage protection: No With miniature fuse: No Special power supply: Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastering: Mounting with claw and screw Material quality: Thermoplastic Halogen free:	With signal lamp:	No
Imprint/indication:NoneWith hinged lid:NoWith enhanced contact protection:YesLabel space/information surface:NoColour:WhiteRAL-number (similar):9016Metallic colour:NoTransparent:NoLockable:NoEject-mechanism:NoInsulated mounting:YesWith function lighting:NoWith orientation lighting:YesOver voltage protection:NoFault current protection:NoMounting method:Flush mounted (plaster)Type of fastening:Mounting with claw and screwMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesSurface protection:LacqueredSurface finishing:MattAnti-bacterial treatment:NoWith on/off switch:Yes	Number of units:	1
With hinged lid:NoWith enhanced contact protection:YesLabel space/information surface:NoColour:WhiteRAL-number (similar):9016Metallic colour:NoTransparent:NoLockable:NoEject-mechanism:NoInsulated mounting:YesWith function lighting:NoOver voltage protection:NoFault current protection:NoWith miniature fuse:NoSpecial power supply:Supplementary safety power supply (orange)Mounting method:Flush mounted (plaster)Type of fastening:Mounting with claw and screwMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesSurface protection:LacqueredSurface finishing:MattAnti-bacterial treatment:NoWith loop through function:YesWith on/off switch:No	Number of phases:	1
With enhanced contact protection: Yes Label space/information surface: No Colour: White RAL-number (similar): 9016 Metallic colour: No Transparent: No Lockable: No Eject-mechanism: No With function lighting: Yes With function lighting: No With orientation lighting: Yes Over voltage protection: No Fault current protection: No With miniature fuse: No Special power supply: Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastening: Mounting with claw and screw Material: Plastic Material quality: Thermoplastic Halogen free: Yes Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No With loop through function: Yes	Imprint/indication:	None
Label space/information surface: White RAL-number (similar): 9016 Metallic colour: No Transparent: No Lockable: No Lockable: No Insulated mounting: Yes With function lighting: No With orientation lighting: No With miniature fuse: No Special power supply: Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastening: Mounting with claw and screw Material: Plastic Material quality: Thermoplastic Halogen free: Yes Surface protection: No Surface protection: Acquered Surface protection: Acquered Surface protection: No Matth miniature fuse: No Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastening: Mounting with claw and screw Material: Plastic Material quality: Thermoplastic Halogen free: Yes Surface protection: Lacquered Surface protection: Mattheatment: No Mith loop through function: Yes With on/off switch: No	With hinged lid:	No
Colour:WhiteRAL-number (similar):9016Metallic colour:NoTransparent:NoLockable:NoEject-mechanism:NoInsulated mounting:YesWith function lighting:NoWith orientation lighting:YesOver voltage protection:NoFault current protection:NoWith miniature fuse:NoSpecial power supply:Supplementary safety power supply (orange)Mounting method:Flush mounted (plaster)Type of fastening:Mounting with claw and screwMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesSurface protection:LacqueredSurface protection:LacqueredAnti-bacterial treatment:NoWith loop through function:YesWith on/off switch:No	With enhanced contact protection:	Yes
RAL-number (similar):9016Metallic colour:NoTransparent:NoLockable:NoEject-mechanism:NoInsulated mounting:YesWith function lighting:NoWith orientation lighting:YesOver voltage protection:NoFault current protection:NoWith miniature fuse:NoSpecial power supply:Supplementary safety power supply (orange)Mounting method:Flush mounted (plaster)Type of fastening:Mounting with claw and screwMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesSurface protection:LacqueredSurface protection:MattAnti-bacterial treatment:NoWith loop through function:YesWith on/off switch:No	Label space/information surface:	No
Metallic colour:NoTransparent:NoLockable:NoEject-mechanism:NoInsulated mounting:YesWith function lighting:NoWith orientation lighting:YesOver voltage protection:NoFault current protection:NoWith miniature fuse:NoSpecial power supply:Supplementary safety power supply (orange)Mounting method:Flush mounted (plaster)Type of fastening:Mounting with claw and screwMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesSurface protection:LacqueredSurface finishing:MattAnti-bacterial treatment:NoWith loop through function:YesWith on/off switch:No	Colour:	White
Transparent: Lockable: No Eject-mechanism: No Insulated mounting: Yes With function lighting: No With orientation lighting: Yes Over voltage protection: No Fault current protection: No Special power supply: Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastening: Mounting with claw and screw Material: Plastic Material quality: Halogen free: Yes Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No With loop through function: Yes With on/off switch: No	RAL-number (similar):	9016
Lockable:NoEject-mechanism:NoInsulated mounting:YesWith function lighting:NoWith orientation lighting:YesOver voltage protection:NoFault current protection:NoWith miniature fuse:NoSpecial power supply:Supplementary safety power supply (orange)Mounting method:Flush mounted (plaster)Type of fastening:Mounting with claw and screwMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesSurface protection:LacqueredSurface finishing:MattAnti-bacterial treatment:NoWith loop through function:YesWith on/off switch:No	Metallic colour:	No
Eject-mechanism: No Insulated mounting: Yes With function lighting: No With orientation lighting: Yes Over voltage protection: No Fault current protection: No With miniature fuse: No Special power supply: Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastening: Mounting with claw and screw Material: Plastic Material quality: Thermoplastic Halogen free: Yes Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No With loop through function: Yes With on/off switch: No	Transparent:	No
Insulated mounting: With function lighting: No With orientation lighting: Over voltage protection: No Fault current protection: No With miniature fuse: No Special power supply: Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastening: Mounting with claw and screw Material: Plastic Material quality: Thermoplastic Halogen free: Yes Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No With loop through function: Yes With on/off switch: No	Lockable:	No
With function lighting: With orientation lighting: Yes Over voltage protection: No Fault current protection: No With miniature fuse: No Special power supply: Supplementary safety power supply (orange) Mounting method: Flush mounted (plaster) Type of fastening: Mounting with claw and screw Material: Plastic Material quality: Thermoplastic Halogen free: Yes Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No With loop through function: Yes With on/off switch: No	Eject-mechanism:	No
With orientation lighting: Over voltage protection: No Fault current protection: No With miniature fuse: No Special power supply: Mounting method: Type of fastening: Material: Material quality: Halogen free: Surface protection: Surface finishing: Matt Anti-bacterial treatment: With loop through function: With on/off switch: No No No No No No No No No N	Insulated mounting:	Yes
Over voltage protection: Fault current protection: No With miniature fuse: No Special power supply: Mounting method: Type of fastening: Material: Material quality: Halogen free: Surface protection: Surface finishing: Mathi-bacterial treatment: With loop through function: With on/off switch: No No No No No No No No No N	With function lighting:	No
Fault current protection: With miniature fuse: No Special power supply: Mounting method: Type of fastening: Material: Material quality: Halogen free: Surface protection: Surface finishing: Mith loop through function: With on/off switch: No No Supplementary safety power supply (orange) Mounting with claw and screw Mounting with claw and screw Mounting with claw and screw Haus and screw Yes Lacquered Yes Surface finishing: Matt No	With orientation lighting:	Yes
With miniature fuse:NoSpecial power supply:Supplementary safety power supply (orange)Mounting method:Flush mounted (plaster)Type of fastening:Mounting with claw and screwMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesSurface protection:LacqueredSurface finishing:MattAnti-bacterial treatment:NoWith loop through function:YesWith on/off switch:No	Over voltage protection:	No
Special power supply:Supplementary safety power supply (orange)Mounting method:Flush mounted (plaster)Type of fastening:Mounting with claw and screwMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesSurface protection:LacqueredSurface finishing:MattAnti-bacterial treatment:NoWith loop through function:YesWith on/off switch:No	Fault current protection:	No
Mounting method: Type of fastening: Mounting with claw and screw Material: Plastic Material quality: Thermoplastic Halogen free: Yes Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No With loop through function: With on/off switch: No	With miniature fuse:	No
Type of fastening: Material: Plastic Material quality: Thermoplastic Halogen free: Yes Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No With loop through function: With on/off switch: Mounting with claw and screw Mounting with claw and screw Matt Thermoplastic Yes Yes No No	Special power supply:	Supplementary safety power supply (orange)
Material: Material quality: Thermoplastic Halogen free: Yes Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No With loop through function: With on/off switch: No	Mounting method:	Flush mounted (plaster)
Material quality:ThermoplasticHalogen free:YesSurface protection:LacqueredSurface finishing:MattAnti-bacterial treatment:NoWith loop through function:YesWith on/off switch:No	Type of fastening:	Mounting with claw and screw
Halogen free: Surface protection: Lacquered Surface finishing: Matt Anti-bacterial treatment: No With loop through function: With on/off switch: No	Material:	Plastic
Surface protection: Surface finishing: Anti-bacterial treatment: With loop through function: With on/off switch: No	Material quality:	Thermoplastic
Surface finishing: Matt Anti-bacterial treatment: No With loop through function: Yes With on/off switch: No	Halogen free:	Yes
Anti-bacterial treatment: With loop through function: Yes With on/off switch: No	Surface protection:	Lacquered
With loop through function: Wes With on/off switch: No	Surface finishing:	Matt
With on/off switch: No	Anti-bacterial treatment:	No
	With loop through function:	Yes
Rotated central insert: No	With on/off switch:	No
	Rotated central insert:	No

© ABB 2025 **Business ID** 0763403-0 www.installationmaterials.com **Customer service** puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange** +358 10 22 11

Product CardSocket outlet, Schuko, 1-gang, shuttered, screwless terminals, LED light, matt white



Impact strength:	IK03
Device width:	71 mm
Device height:	71 mm
Device depth:	46.5 mm
Min. depth of built-in installation box:	32 mm
Compatible with Apple HomeKit:	No
Compatible with Amazon Alexa:	No
Compatible with Google Assistant:	No
IFTTT support available:	No
With Wi-Fi signal repeater:	No
With built-in bluetooth speaker:	No

© ABB 2025 **Business ID** 0763403-0 www.installationmaterials.com **Customer service** puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange** +358 10 22 11