

LED dim. insert flex, 1 g

Type: 64851 U-500

Product ID: 2CKA006500A0013

GTIN: 4011395294208



Technical specification

Classification

Suitable for degree of protection (IP):	IP20
---	------

Packing

Package:	1/10
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000025
Assembly arrangement:	Basic element
Method of operation:	Push button
App control via Bluetooth:	No
Dimming phase cut-on:	Yes
Dimming phase cut-off:	Yes
Serial dimmer:	No
Type of load:	Universal and LED Retrofit
Substation input:	Yes
Light value memory:	Yes

Product Card

LED dim. insert flex, 1 g



Applicable with button:	Yes
Applicable with movement sensor:	Yes
Applicable with presence indicator:	Yes
Applicable with time switch/timer:	Yes
Applicable with transmission button:	Yes
Applicable with infrared button:	No
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	Black
Transparent:	No
Impact strength:	IK00
Nominal voltage:	230 V
Control voltage:	230 V
Max. switching power LED:	240 W
Connection type:	Other
Device width:	71 mm
Device height:	71 mm
Device depth:	30 mm
Min. depth of built-in installation box:	28 mm
Compatible with Apple HomeKit:	No
Compatible with Google Assistant:	No
Compatible with Amazon Alexa:	No
IFTTT support available:	No