

# LED-Dimmer

LED dimmer, rotary 2-100VA, with neon lamp, Impressivo



**Type:** 6523URCGL-84-103

**GTIN:** 4011395232125

Optimized for dimming of Philips retrofit LEDs (LEDi). With rotary control, soft-catch and with leading edge control.  
For incandescent lamps, 230V tungsten halogen lamps and low-voltage halogen lamps with conventional transformers or electronic (LC) transformers and dimmable halogen energy-saving lamps.  
Mix operaton of LEDi with conventional loads possible.  
Low-noise level by MOSFET transistors.  
With electronic short-circuit protection.  
With electronic overload protection.  
With adjustable minimum brightness.  
Product includes insert, center plate and frame.

Note!  
There might be limitations from transformer producers on how many dimmable LED bulbs can be connected behind one transformer

## Technical specification

### General Information

Product ID:	2CKA006512A0347
-------------	-----------------

### Packing

Package:	1/10
Unit:	PCS

### ETIM Data

Assembly arrangement:	Basic element with central cover plate
-----------------------	--

# Product Card

LED dimmer, rotary 2-100VA, with neon lamp, Impressivo



Method of operation:	Turn/push button
Type of load:	Universal and LED Retrofit
Minimum brightness controllable:	Yes
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	No
Surface protection:	Untreated
Surface finishing:	Glossy
Colour:	White
RAL-number (similar):	9016
Suitable for degree of protection (IP):	IP21
Impact strength:	IK00
Nominal voltage:	207...253 V
Frequency:	50...60 Hz
Control voltage:	220...240 V
Connection type:	Screwed terminal
Core cross section:	1.0...2.5 mm <sup>2</sup>
Device width:	71 mm
Device height:	71 mm
Device depth:	44 mm
Min. depth of built-in installation box:	20 mm
Compatible with Apple HomeKit:	No
Compatible with Google Assistant:	No
Compatible with Amazon Alexa:	No
IFTTT support available:	No