

Dimmer

DALI potentiometer insert

Type: 2117 U-500

Product ID: 2CKA006599A2987

GTIN: 4011395152218



For DALI broadcast service (via central telegram).
For switching and dimming up to 64 DALI- devices like electronic ballasts and transformers with DALI-interface.
With rotary control and ON/OFF push operation.
Fool proved.
Brightness power-on level and background brightness level adjustable, buffered.
With integrated LED illumination for orientation.
Color of orientation light adjustable (18 presets and OFF).
Up to 5 potentiometers are connectable in parallel.
Max. current consumption: 15 mA.
Not suitable in combination with other DALI-sensors.
An additional DALI power supply is needed, e.g. by Tridonic, Philips, Helvar or 2117/11 U.
Max. DALI-cable length: 300 m (1, 5 - 2, 5 mm²).
Without cover plate.
Protection class (Device): IP 20
Temperature range (Device): 0 °C to 35 °C

Technical specification

Packing

Package:	1/10
Unit:	PCS

Product Card

DALI potentiometer insert



ETIM Data

Mounting method:	Flush mounted (plaster)
Control current:	15 mA
Method of operation:	Turn/push button
Substation input:	Yes
Light value memory:	Yes
Min. depth of built-in installation box:	28.5 mm
Device width:	71 mm
Device height:	71 mm
Device depth:	51 mm
Metallic colour:	No
Compatible with Apple HomeKit:	No
Compatible with Google Assistant:	No
Compatible with Amazon Alexa:	No
IFTTT support available:	No