

Product Card

Socket outlet, ProDuct, 2xShuko, white



Socket outlet

Socket outlet, ProDuct, 2xShuko, white

Type: AUD10-214

Product ID: 2TKA00000809

GTIN: 6438199002019



The socket-outlet is approved for extending a branch circuit with solid and rigid wires. When chaining several AUD10-socket-outlets, the recommended length of intermediate cables is 120 mm. The end piece package AUD30 or AUD31 is required for each socket group. The depth of box is 45 mm.

Technical specification

Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

Classification

Suitable for degree of protection (IP):	IP20
---	------

Packing

Package:	10/100
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

Product Card

Socket outlet, ProDuct, 2xShuko, white



ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	No
Number of units:	2
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9010
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Wall duct
Type of fastening:	Snap mounting (engagement)
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No

Product Card

Socket outlet, ProDuct, 2xShuko, white



Frequency:	50 Hz
Device width:	45 mm
Device height:	85 mm
Device depth:	80 mm