

## Product Card

Socket outlet, ProDuct, 2xShuko, "DATA" label, white



# Socket outlet

Socket outlet, ProDuct, 2xShuko, "DATA" label, white



**Type:** AUD10-214D

**Product ID:** 2TKA00000811

**GTIN:** 6438199002033



The socket-outlet is approved for extending a branch circuit with solid and rigid cables. When chaining several AUD10-socket-outlets, the recommended length of intermediate cables is 120 mm. The end piece package AUD30 or AUD31 is required for each socket group. The depth of box is 45 mm.

## Technical specification

### Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

### Classification

Suitable for degree of protection (IP):	IP20
---	------

### Packing

Package:	10/100
Unit:	PCS

### ETIM Data

© ABB 2024

Business ID 0763403-0

[www.installationmaterials.com](http://www.installationmaterials.com)

**Customer service**

puh. +358 10 222 1999

[contact.center@fi.abb.com](mailto:contact.center@fi.abb.com)

**ABB Exchange**

+358 10 22 11

# Product Card

Socket outlet, ProDuct, 2xShuko, "DATA" label, white



Number of active pins (round):	2
With signal lamp:	No
Number of units:	2
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9010
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Wall duct
Type of fastening:	Snap mounting (engagement)
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No

# Product Card

Socket outlet, ProDuct, 2xShuko, "DATA" label, white



Frequency:	50 Hz
Device width:	45 mm
Device height:	85 mm
Device depth:	80 mm