

## Product Card

Push button, 4/2-gang, Impressivo, white




# Push button

Push button, 4/2-gang, Impressivo, white

**Type:** FAP1204-84

**Product ID:** 2TKA00000915

**GTIN:** 6438199002309



4/2-gang push button panel to control bistable relays or electronic control systems. Load capacity 1A AC/DC. White LED-light with adjustable illumination. Installation on surface or on top of a standard flush mounting box.

## Technical specification

### Electrical quantities

|                    |              |
|--------------------|--------------|
| Nominal voltage:   | 24 V         |
| Operating voltage: | 5-24 V ac/dc |

### Classification

|   |      |
|---|------|
| Suitable for degree of protection (IP): | IP20 |
|---|------|

### Thermal conditions

|                        |             |
|------------------------|-------------|
| Operating temperature: | 5 ... 40 °C |
|------------------------|-------------|

### Signal products

|                                   |                                     |
|-----------------------------------|-------------------------------------|
| Loading capacity of switch (max): | 1 mA - 1 A ac/dc res. 5 - 24V ac/dc |
| Current drain of signal lamp:     | 10 mA ac/17 mA dc                   |

# Product Card

Push button, 4/2-gang, Impressivo, white



## Packing

|          |               |
|----------|---------------|
| Package: | 1/10/100/1200 |
| Unit:    | PCS           |

## ETIM Data

|  |  |
|--|--|
| ETIM Version:                                  | ETIM-9.0                               |
| ETIM Class:                                    | EC000029                               |
| Assembly arrangement:                          | Basic element with central cover plate |
| Model:   | Group push button                      |
| Method of operation:                           | Push button                            |
| Number of contacts as normally closed contact: | 4                                      |
| Contactless type:                              | No                                     |
| Number of rockers:                             | 4                                      |
| Number of poles:                               | 1                                      |
| Rated current:                                 | 1 A                                    |
| With lighting:                                 | No                                     |
| Feedback-signal contact:                       | Yes                                    |
| Connection type:                               | Screwed terminal                       |
| Mounting method:                               | Flush mounted (plaster)                |
| Type of fastening:                             | Screw mounting                         |
| Material:                                      | Plastic                                |
| Material quality:                              | Thermoplastic                          |
| Halogen free:                                  | Yes                                    |
| Anti-bacterial treatment:                      | No                                     |
| Surface protection:                            | Untreated                              |
| Surface finishing:                             | Glossy                                 |
| Colour:  | White                                  |
| RAL-number (similar):                          | 9016                                   |
| Transparent:                                   | No                                     |
| Label space/information surface:               | No                                     |
| Imprint:                                       | None                                   |
| Impact strength:                               | IK00                                   |
| Device width:                                  | 71 mm                                  |

## Product Card

Push button, 4/2-gang, Impressivo, white



|  |       |
|--|-------|
| Device height:                           | 71 mm |
| Device depth:                            | 20 mm |
| Min. depth of built-in installation box: | 21 mm |
| Compatible with Apple HomeKit:           | No    |
| Compatible with Google Assistant:        | No    |
| Compatible with Amazon Alexa:            | No    |
| IFTTT support available:                 | No    |