

## Product Card

Push button, 4/2-gang, Impressivo, white



# Push button

Push button, 4/2-gang, Impressivo, white



**Type:** FAP1204-84

**Product ID:** 2TKA00000915

**GTIN:** 6438199002309



4/2-gang push button panel to control bistable relays or electronic control systems. Load capacity 1A AC/DC. White LED-light with adjustable illumination. Installation on surface or on top of a standard flush mounting box.

## Technical specification

### Classification

Enclosure class:	IP20
------------------	------

### Thermal conditions

Operating temperature:	5 ... 40 °C
------------------------	-------------

### Signal products

Loading capacity of switch (max):	1 mA - 1 A ac/dc res. 5 - 24V ac/dc
Current drain of signal lamp:	10 mA ac/17 mA dc

### Electrical quantities

Operating voltage:	5-24 V ac/dc
--------------------	--------------

# Product Card

Push button, 4/2-gang, Impressivo, white



## Packing

Package:	1/10/100/1200
Unit:	PCS

## ETIM Data

Assembly arrangement:	Basic element with central cover plate
Model:	Group push button
Method of operation:	Push button
Number of contacts as normally closed contact:	4
Contactless type:	No
Number of rockers:	4
Number of poles:	1
Nominal voltage:	24 V
Rated current:	1 A
With lighting:	No
Feedback-signal contact:	Yes
Connection type:	Screwed terminal
Mounting method:	Flush mounted (plaster)
Type of fastening:	Screw mounting
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Anti-bacterial treatment:	No
Surface protection:	Untreated
Surface finishing:	Glossy
Colour:	White
RAL-number (similar):	9016
Transparent:	No
Label space/information surface:	No
Imprint:	None
Suitable for degree of protection (IP):	IP20
Impact strength:	IK00
Device width:	71 mm

## Product Card

Push button, 4/2-gang, Impressivo, white



Device height:	71 mm
Device depth:	20 mm
Min. depth of built-in installation box:	21 mm
Compatible with Apple HomeKit:	No
Compatible with Google Assistant:	No
Compatible with Amazon Alexa:	No
IFTTT support available:	No