

Product Card

1-gang 2-way switch, 16AX/250V, Impressivo, 2 X-terminals, aluminum



Switch

1-gang 2-way switch, 16AX/250V,
Impressivo, 2 X-terminals, aluminum



Type: 1066A-83

Product ID: 2TKA00001603

GTIN: 6438199003245



Surface mounting switch with screwless terminals. The terminals are for max 2 solid or rigid wires. Including switch insert, rocker, surface mounting frame and bottom.

Technical specification

Electrical quantities

Nominal voltage:	250 V
Rated current:	16 AX

Classification

Suitable for degree of protection (IP):	IP21
Protection class:	IP21

Packing

Package:	1/10/100/1200
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

Product Card

1-gang 2-way switch, 16AX/250V, Impressivo, 2 X-terminals, aluminum



ETIM Class:	EC001590
Wiring system:	Two-way switch
Method of operation:	Rocker/button
Assembly arrangement:	Basic element with complete housing
Push button switch:	No
Number of rockers:	1
Mounting method:	Surface mounted (plaster)
Type of fastening:	Screw mounting
With mounting plate:	Yes
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Anti-bacterial treatment:	No
Surface protection:	Lacquered
Surface finishing:	Matt
Colour:	Aluminium
RAL-number (similar):	9006
Label space/information surface:	No
Function lighting:	Control and orientation
Rated current:	16 A
Switching current for fluorescent lamps:	16 AX
Feedback-signal contact:	No
Connection type:	Other
Washing machine switch:	No
Device width:	85 mm
Device height:	35 mm
Device depth:	85 mm
Built-in depth:	18 mm
Min. depth of built-in installation box:	18 mm