

Product Card

Mounting box for hollow walls, hole Ø74 mm



Mounting box

Mounting box for hollow walls, hole Ø74 mm



Type: AUS74.2

Product ID: 2TKA00003482

GTIN: 6438199005041



AUS74.2 is a front-mounted mounting box with a telescopic bottom part for walls of 1–3 plasterboards (wall thickness 9–39 mm). Due to the telescopic bottom part, the depth of the box can be adjusted between 54mm and 70 mm. Mounting hole diameter 73–74 mm (normal box drill).

The protection rating of the box is IP3X. Made from halogen-free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test

according to the IEC/EN 60670 standard: 2005 (850 °C).

Technical specification

Electrical quantities

| | |
|--------------------|-------|
| Operating voltage: | 400 V |
|--------------------|-------|

Thermal conditions

| | |
|------------------------|---------------|
| Operating temperature: | -25 ... 90 °C |
|------------------------|---------------|

Dimensions

| | |
|-------------------|----------|
| For plastic pipe: | Ø16/20mm |
|-------------------|----------|

Product Card

Mounting box for hollow walls, hole Ø74 mm



Packing

| | |
|----------|-----|
| Package: | 60 |
| Unit: | PCS |

ETIM Data

| | |
|--|--------------------------------------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC002601 |
| Mounting method: | Flush mounted (plaster) |
| Shape: | Round |
| Construction type: | Device connection box (round/square) |
| Model: | Single |
| Provided with revolving ring: | No |
| Connectable: | Yes |
| Equipped with: | None |
| Diameter: | 74 mm |
| Length: | 73 mm |
| Width: | 73 mm |
| Depth: | 73 mm |
| Inner depth: | 52 mm |
| For number of electric fittings: | 1 |
| Mounting switching equipment: | Screwing |
| With screws: | Yes |
| Housing feed-through by break-out opening: | No |
| Housing feed-through by seal membrane: | No |
| Housing feed-through by nozzle: | No |
| Housing feed-through by step membrane: | No |
| For tube diameter: | 20 mm |
| Suitable for cable diameter: | 8 mm |
| Pipe locking: | Yes |
| Pipe locking optional: | No |
| Inlet from the rear: | Yes |
| Material: | Plastic |
| Halogen free: | Yes |

Product Card

Mounting box for hollow walls, hole Ø74 mm



| | |
|----------------------------|-----------|
| Surface protection: | Untreated |
| Colour: | White |
| Degree of protection (IP): | IP3X |
| Transparent cover: | No |
| Sealable: | No |
| With screening: | No |
| Air tight: | No |
| Clamp position fixed: | No |
| Luminaire hook mounting: | No |
| Special application: | None |