

Product Card

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, black matt



Socket outlet

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, black matt



Type: 302EUJT-885

Product ID: 2TKA00003863

GTIN: 6438199005348



There are terminals for each contact of the socket outlet for max 4 rigid wires. No X-terminals. The socket outlet insert without the cover plate is screen-protected. Wery flat construction. Installatin in special 1,5X mounting box.

Technical specification

Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

Classification

Suitable for degree of protection (IP):	IP21
---	------

Packing

Package:	1/10/100/1200
Unit:	PCS

ETIM Data

© ABB 2024

Business ID 0763403-0

www.installationmaterials.com

Customer service

puh. +358 10 222 1999

contact.center@fi.abb.com

ABB Exchange

+358 10 22 11

Product Card

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, black matt



Model:	Protective contact (type F)
Protective contact:	Yes
Protective earth pin round:	No
With signal lamp:	No
With built-in USB power supply:	No
Number of units:	2
Number of modules (module system):	1
Number of phases:	1
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	Black
RAL-number (similar):	9005
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	Yes
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Lacquered
Surface finishing:	Matt
Anti-bacterial treatment:	No

Product Card

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, black matt



With on/off switch:	No
With loop through function:	No
Rotated central insert:	No
Frequency:	50 Hz
Device width:	120 mm
Device height:	80 mm
Device depth:	40 mm
Min. depth of built-in installation box:	17 mm