

---

# Countdown timer

Basic timer, matt black



**Type:** T210-885

**Product ID:** 2TKA00004108

**GTIN:** 6438199008059



Fixed time options: 15min, 30min, 1h, 2h, 4h and 8h. Exchangeable labels with the time options to mark center plate with selected time. 230 VAC, 50Hz, 0 - 40C, IP21, 2-pole wiring. 10A resistiv load (2300W), 2AX-load (e.g. fluorescent lamp). Screw terminals max 2,5mm<sup>2</sup>. Signal light when active.

## Technical specification

### Dimensions

|                       |       |
|-----------------------|-------|
| A:                    | 70 mm |
| B:                    | 70 mm |
| C:                    | 32 mm |
| Recessing dimensions: | 18 mm |

### Classification

|                   |      |
|-------------------|------|
| Protection class: | IP21 |
|-------------------|------|

### Packing

|          |               |
|----------|---------------|
| Package: | 1/10/100/1200 |
| Unit:    | PCS           |

# Product Card

Basic timer, matt black



## ETIM Data

|  |  |
|--|--|
| Assembly arrangement:                        | Basic element with central cover plate |
| Number of contacts as normally open contact: | 1                                      |
| Model:                                       | Electronic                             |
| Mounting method:                             | Other                                  |
| Type of fastening:                           | Mounting with screw                    |
| Material:                                    | Plastic                                |
| Material quality:                            | Thermoplastic                          |
| Surface protection:                          | Untreated                              |
| Colour:                                      | Black                                  |
| Transparent:                                 | No                                     |
| Suitable for degree of protection (IP):      | IP20                                   |
| Shortest switching interval:                 | 15 min                                 |
| Random generator:                            | No                                     |
| Nominal voltage:                             | 230 V                                  |
| Astro program:                               | No                                     |
| Substation input:                            | No                                     |
| Rated current:                               | 10 A                                   |
| With brightness sensor connection:           | No                                     |
| Max. power:                                  | 2300 W                                 |
| Compatible with Apple HomeKit:               | No                                     |
| Compatible with Google Assistant:            | No                                     |
| Compatible with Amazon Alexa:                | No                                     |
| IFTTT support available:                     | No                                     |
| Built-in depth:                              | 18 mm                                  |
| Min. depth of built-in installation box:     | 18 mm                                  |
| Device width:                                | 71 mm                                  |
| Device height:                               | 34 mm                                  |
| Device depth:                                | 71 mm                                  |