

## Product Card

Height 68 mm, screw c/c distance 60 mm



# Mounting box

Height 68 mm, screw c/c distance 60 mm

**Type:** AUB60

**Product ID:** 2TKA00004663

**GTIN:** 6438199008851



Mounting box AUB60 is especially designed for off site and on site casting applications. Box height is 68 mm. Box has two inlets with locking springs for 20 or 25 mm conduits. Additional inlets can be attached to other sides without need of any tooling. The mounting box includes a rotating, steplessly adjustable extension ring. The extension ring can be tilted 0-4°. Box combinations can be created without additional accessories and box has large inside space. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (650 °C). Maximum number of conductors is 30 pcs.

## Technical specification

### Thermal conditions

|                        |               |
|------------------------|---------------|
| Operating temperature: | -25 ... 90 °C |
|------------------------|---------------|

### Packing

|          |     |
|----------|-----|
| Package: | 50  |
| Unit:    | PCS |

### ETIM Data

|               |          |
|---------------|----------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class:   | EC002601 |

© ABB 2025

Business ID 0763403-0

[www.installationmaterials.com](http://www.installationmaterials.com)

Customer service

puh. +358 10 222 1999

[contact.center@fi.abb.com](mailto:contact.center@fi.abb.com)

ABB Exchange

+358 10 22 11

# Product Card

Height 68 mm, screw c/c distance 60 mm



|  |                                      |
|--|--------------------------------------|
| Mounting method:                           | Concrete building                    |
| Shape:                                     | Round                                |
| Construction type:                         | Device connection box (round/square) |
| Model:                                     | Single                               |
| Provided with revolving ring:              | Yes                                  |
| Connectable:                               | Yes                                  |
| Equipped with:                             | None                                 |
| Diameter:                                  | 71 mm                                |
| Length:                                    | 167 mm                               |
| Width:                                     | 98 mm                                |
| Depth:                                     | 167 mm                               |
| Inner depth:                               | 63 mm                                |
| For number of electric fittings:           | 1                                    |
| Mounting switching equipment:              | Screwing                             |
| With screws:                               | Yes                                  |
| Housing feed-through by break-out opening: | Yes                                  |
| Housing feed-through by seal membrane:     | No                                   |
| Housing feed-through by nozzle:            | Yes                                  |
| Housing feed-through by step membrane:     | No                                   |
| For tube diameter:                         | 20/25 mm                             |
| Pipe locking:                              | Yes                                  |
| Pipe locking optional:                     | No                                   |
| Inlet from the rear:                       | No                                   |
| Number of inlets:                          | 8                                    |
| Number of included spouts:                 | 2                                    |
| Material:                                  | Plastic                              |
| Halogen free:                              | Yes                                  |
| Surface protection:                        | Untreated                            |
| Colour:                                    | White                                |
| Degree of protection (IP):                 | IP3X                                 |
| Cover model:                               | Construction protective cover        |
| Transparent cover:                         | No                                   |
| Cover attachment:                          | Snapped on                           |
| Sealable:                                  | No                                   |

# Product Card

Height 68 mm, screw c/c distance 60 mm



|                          |      |
|--------------------------|------|
| With screening:          | No   |
| Air tight:               | No   |
| Clamp position fixed:    | No   |
| Luminaire hook mounting: | No   |
| Special application:     | None |