

Junction box

AUB67M Junction box White IP3X

Type: AUB67M

Product ID: 2TKA00005323

GTIN: 6438199013916













Junction box AUB67M is especially designed for off site and on site casting applications. Box height is 96 mm. Box has several fixed inlets with locking springs to two directions (4 x 20 mm and 4 x 20/25 mm). The mounting box includes a rotating installation ring, has large inside space and removable back cover. Made of halogen free material (IEC/61249-2-21).

Technical specification

Packing

Package:	27/324
Unit:	PCS

ETIM Data

Mounting method:	Concrete building
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Single
Provided with revolving ring:	Yes
Connectable:	Yes
Diameter:	125 mm
Length:	200 mm

© ABB 2024

Business ID 0763403-0

ABB Exchange

Product Card

AUB67M Junction box White IP3X



Depth: 200 mm Inner depth: 94 mm For number of electric fittings: 1 Mounting switching equipment: 5crewing With screws: Yes Housing feed-through by break-out opening: Yes Housing feed-through by seal membrane: No Housing feed-through by step membrane: No For tube diameter: 20/25 mm Pipe locking: Yes Pipe locking optional: No Number of inlets: 12 Number of included spouts: 8 Material: Plastic Halogen free: Yes Surface protection: Untreated Colour: White Degree of protection (IP): IP3X Cover model: Construction protective cover Transparent cover: No Sealable: No With screening: No Clar tight: No Clar tight: No Clar tight: No Clar tight: No <th< th=""><th>Width:</th><th>125 mm</th></th<>	Width:	125 mm
For number of electric fittings: Mounting switching equipment: With screws: Yes Housing feed-through by break-out opening: Housing feed-through by seal membrane: Housing feed-through by seal membrane: Housing feed-through by step membrane: No For tube diameter: 20/25 mm Pipe locking: Yes Pipe locking: No Number of inlets: 12 Number of included spouts: Material: Halogen free: Yes Surface protection: Untreated Colour: White Degree of protection (IP): Iransparent cover: No Cover model: Cover attachment: Sealable: No With screening: No Air tight: No Clamp position fixed: No Clamp position fixed: No No Clamp position fixed: No No Iransparent cover: No Clamp position fixed: No No Clamp position fixed: No No Clamp position fixed: No No Cover attachment: No Cover attachment: No Clamp position fixed: No No Clamp position fixed: No No Clamp position fixed: No No Cover attachmenting: No No Clamp position fixed: No No Clamp position fixed: No No Cover attachmenting: No No Clamp position fixed: No No Cuminatire hook mounting: No No Cover attachmenting: No No Cuminatire hook mounting: No Cover attachmenting: No Cover	Depth:	200 mm
Mounting switching equipment:ScrewingWith screws:YesHousing feed-through by break-out opening:YesHousing feed-through by seal membrane:NoHousing feed-through by nozzle:YesHousing feed-through by step membrane:NoFor tube diameter:20/25 mmPipe locking:YesPipe locking optional:NoNumber of inlets:12Number of included spouts:8Material:PlasticSurface protection:UntreatedColour:WhiteDegree of protection (IP):1P3XCover model:Construction protective coverTransparent cover:NoCover attachment:Snapped onSealable:NoWith screening:NoAir tight:NoClamp position fixed:NoLuminaire hook mounting:No	Inner depth:	94 mm
With screws:YesHousing feed-through by break-out opening:YesHousing feed-through by seal membrane:NoHousing feed-through by nozzle:YesHousing feed-through by step membrane:NoFor tube diameter:20/25 mmPipe locking:YesPipe locking optional:NoNumber of inlets:12Number of included spouts:8Material:PlasticHalogen free:YesSurface protection:UntreatedColour:WhiteDegree of protection (IP):IP3XCover model:Construction protective coverTransparent cover:NoCover attachment:Snapped onSealable:NoWith screening:NoAir tight:NoClamp position fixed:NoLuminaire hook mounting:No	For number of electric fittings:	1
Housing feed-through by break-out opening:YesHousing feed-through by seal membrane:NoHousing feed-through by nozzle:YesHousing feed-through by step membrane:NoFor tube diameter:20/25 mmPipe locking:YesPipe locking optional:NoNumber of inlets:12Number of included spouts:8Material:PlasticHalogen free:YesSurface protection:UntreatedColour:WhiteDegree of protection (IP):IP3XCover model:Construction protective coverTransparent cover:NoCover attachment:Snapped onSealable:NoWith screening:NoAir tight:NoClamp position fixed:NoLuminaire hook mounting:No	Mounting switching equipment:	Screwing
Housing feed-through by seal membrane:NoHousing feed-through by nozzle:YesHousing feed-through by step membrane:NoFor tube diameter:20/25 mmPipe locking:YesPipe locking optional:NoNumber of inlets:12Number of included spouts:8Material:PlasticHalogen free:YesSurface protection:UntreatedColour:WhiteDegree of protection (IP):IP3XCover model:Construction protective coverTransparent cover:NoCover attachment:Snapped onSealable:NoWith screening:NoAir tight:NoClamp position fixed:NoLuminaire hook mounting:No	With screws:	Yes
Housing feed-through by nozzle:YesHousing feed-through by step membrane:NoFor tube diameter:20/25 mmPipe locking:YesPipe locking optional:NoNumber of inlets:12Number of included spouts:8Material:PlasticHalogen free:YesSurface protection:UntreatedColour:WhiteDegree of protection (IP):IP3XCover model:Construction protective coverTransparent cover:NoCover attachment:Snapped onSealable:NoWith screening:NoAir tight:NoClamp position fixed:NoLuminaire hook mounting:No	Housing feed-through by break-out opening:	Yes
Housing feed-through by step membrane:NoFor tube diameter:20/25 mmPipe locking:YesPipe locking optional:NoNumber of inlets:12Number of included spouts:8Material:PlasticHalogen free:YesSurface protection:UntreatedColour:WhiteDegree of protection (IP):IP3XCover model:Construction protective coverTransparent cover:NoCover attachment:Snapped onSealable:NoWith screening:NoAir tight:NoClamp position fixed:NoLuminaire hook mounting:No	Housing feed-through by seal membrane:	No
For tube diameter: 20/25 mm Pipe locking: Yes Pipe locking optional: No Number of inlets: 12 Number of included spouts: 8 Material: Plastic Halogen free: Yes Surface protection: Untreated Colour: White Degree of protection (IP): IP3X Cover model: Construction protective cover Transparent cover: No Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Lumínaire hook mounting: No	Housing feed-through by nozzle:	Yes
Pipe locking: Yes Pipe locking optional: No Number of inlets: 12 Number of included spouts: 8 Material: Plastic Halogen free: Yes Surface protection: Untreated Colour: White Degree of protection (IP): IP3X Cover model: Construction protective cover Transparent cover: No Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Luminaire hook mounting: No	Housing feed-through by step membrane:	No
Pipe locking optional: No Number of inlets: 12 Number of included spouts: 8 Material: Plastic Halogen free: Yes Surface protection: Untreated Colour: White Degree of protection (IP): IP3X Cover model: Construction protective cover Transparent cover: No Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Luminaire hook mounting: No	For tube diameter:	20/25 mm
Number of inlets:12Number of included spouts:8Material:PlasticHalogen free:YesSurface protection:UntreatedColour:WhiteDegree of protection (IP):IP3XCover model:Construction protective coverTransparent cover:NoCover attachment:Snapped onSealable:NoWith screening:NoAir tight:NoClamp position fixed:NoLuminaire hook mounting:No	Pipe locking:	Yes
Number of included spouts: 8 Material: Plastic Halogen free: Yes Surface protection: Untreated Colour: White Degree of protection (IP): IP3X Cover model: Construction protective cover Transparent cover: No Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Luminaire hook mounting: No	Pipe locking optional:	No
Material:PlasticHalogen free:YesSurface protection:UntreatedColour:WhiteDegree of protection (IP):IP3XCover model:Construction protective coverTransparent cover:NoCover attachment:Snapped onSealable:NoWith screening:NoAir tight:NoClamp position fixed:NoLuminaire hook mounting:No	Number of inlets:	12
Halogen free: Yes Surface protection: Untreated Colour: White Degree of protection (IP): IP3X Cover model: Construction protective cover Transparent cover: No Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Luminaire hook mounting: No	Number of included spouts:	8
Surface protection: Colour: White Degree of protection (IP): IP3X Cover model: Construction protective cover Transparent cover: No Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Luminaire hook mounting: No No With screening: No	Material:	Plastic
Colour: White Degree of protection (IP): IP3X Cover model: Construction protective cover Transparent cover: No Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Luminaire hook mounting: No	Halogen free:	Yes
Degree of protection (IP): Cover model: Construction protective cover Transparent cover: No Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Luminaire hook mounting: No	Surface protection:	Untreated
Cover model: Transparent cover: No Cover attachment: Sealable: No With screening: No Clamp position fixed: Luminaire hook mounting: Construction protective cover No No No No No No No No No N	Colour:	White
Transparent cover: Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Luminaire hook mounting: No	Degree of protection (IP):	IP3X
Cover attachment: Snapped on Sealable: No With screening: No Air tight: No Clamp position fixed: No Luminaire hook mounting: No	Cover model:	Construction protective cover
Sealable:NoWith screening:NoAir tight:NoClamp position fixed:NoLuminaire hook mounting:No	Transparent cover:	No
With screening: Air tight: No Clamp position fixed: Luminaire hook mounting: No	Cover attachment:	Snapped on
Air tight: No Clamp position fixed: No Luminaire hook mounting: No	Sealable:	No
Clamp position fixed: No Luminaire hook mounting: No	With screening:	No
Luminaire hook mounting: No	Air tight:	No
	Clamp position fixed:	No
Special application: None	Luminaire hook mounting:	No
	Special application:	None

© ABB 2024
Business ID 0763403-0
www.installationmaterials.com

Customer service puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange** +358 10 22 11