

AUB67M

AUB67M Junction box White IP3X

Type: AUB67M
GTIN: 6438199013916



Junction box AUB67M is especially designed for off site and on site casting applications. Box height is 96 mm. Box has several fixed inlets with locking springs to two directions (4 x 20 mm and 4 x 20/25 mm). The mounting box includes a rotating installation ring, has large inside space and removable back cover. Made of halogen free material (IEC/61249-2-21).

Technical specification

General Information

| | |
|-------------|--------------|
| Product ID: | 2TKA00005323 |
|-------------|--------------|

Packing

| | |
|----------|--------|
| Package: | 27/324 |
| Unit: | PCS |

ETIM Data

| | |
|-------------------------------|--------------------------------------|
| Mounting method: | Concrete building |
| Shape: | Round |
| Construction type: | Device connection box (round/square) |
| Model: | Single |
| Provided with revolving ring: | Yes |
| Connectable: | Yes |



| | |
|--|-------------------------------|
| Diameter: | 125 mm |
| Length: | 200 mm |
| Width: | 125 mm |
| Depth: | 200 mm |
| Inner depth: | 94 mm |
| For number of electric fittings: | 1 |
| Mounting switching equipment: | Screwing |
| With screws: | Yes |
| Housing feed-through by break-out opening: | Yes |
| Housing feed-through by seal membrane: | No |
| Housing feed-through by nozzle: | Yes |
| Housing feed-through by step membrane: | No |
| For tube diameter: | 20/25 mm |
| Pipe locking: | Yes |
| Pipe locking optional: | No |
| Number of inlets: | 12 |
| Number of included spouts: | 8 |
| Material: | Plastic |
| Halogen free: | Yes |
| Surface protection: | Untreated |
| Colour: | White |
| Degree of protection (IP): | IP3X |
| Cover model: | Construction protective cover |
| Transparent cover: | No |
| Cover attachment: | Snapped on |
| Sealable: | No |
| With screening: | No |
| Air tight: | No |
| Clamp position fixed: | No |
| Luminaire hook mounting: | No |
| Special application: | None |