

Product Card

1-gang 2-way push switch, Jussi, N-terminal, lens, lamp not included



Push switch

1-gang 2-way push switch, Jussi, N-terminal, lens, lamp not included


Type: 1466AK4

Product ID: 2TKA000237G1

GTIN: 6418677307560



Surface mounting push switch with screwless terminals and rocker with clip-on fastening. The terminals are for max 2 rigid wires.



Technical specification

Electrical quantities

Rated current:	10 A
Rated voltage:	250 V

Classification

Enclosure class:	IP21
------------------	------

Packing

Package:	10/100
Unit:	PCS

ETIM Data

© ABB 2024

Business ID 0763403-0

www.installationmaterials.com

Customer service

puh. +358 10 222 1999

contact.center@fi.abb.com

ABB Exchange

+358 10 22 11

Product Card

1-gang 2-way push switch, Jussi, N-terminal, lens, lamp not included



Assembly arrangement:	Basic element with complete housing
Model:	Single push button
Method of operation:	Push button
Number of contacts as normally open contact:	2
Contactless type:	No
Number of rockers:	1
Number of poles:	1
Nominal voltage:	250 V
Rated current:	10 A
With lighting:	No
Feedback-signal contact:	No
Connection type:	Push-in clamp
Mounting method:	Surface mounted (plaster)
Type of fastening:	Screw mounting
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Anti-bacterial treatment:	No
Surface protection:	Untreated
Colour:	White
RAL-number (similar):	9010
Transparent:	No
Label space/information surface:	No
Imprint:	None
Suitable for degree of protection (IP):	IP21
Impact strength:	IK00
Device width:	72 mm
Device height:	34 mm
Device depth:	72 mm
Min. depth of built-in installation box:	18 mm
Compatible with Apple HomeKit:	No
Compatible with Google Assistant:	No
Compatible with Amazon Alexa:	No
IFTTT support available:	No

Product Card

1-gang 2-way push switch, Jussi, N-terminal, lens, lamp not included



—
© ABB 2024

Business ID 0763403-0

www.installationmaterials.com

—
Customer service

puh. +358 10 222 1999

contact.center@fi.abb.com

—
ABB Exchange

+358 10 22 11