

## Product Card

Socket outlet, Jussi, non-earthed, 1-gang, shuttered, screw terminals



# Socket outlet

Socket outlet, Jussi, non-earthed, 1-gang, shuttered, screw terminals



**Type:** 23-01UC-212

**Product ID:** 2TKA000753G1

**GTIN:** 6410025060110



There are terminals for both contacts of the socket outlet. The terminals are for max 2 rigid wires. No X-terminals.

## Technical specification

### Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

### Classification

Suitable for degree of protection (IP):	IP20
-----------------------------------------	------

### Packing

Package:	10/100
Unit:	PCS

### ETIM Data

Number of active pins (round):	2
With signal lamp:	No

# Product Card

Socket outlet, Jussi, non-earthed, 1-gang, shuttered, screw terminals



Number of units:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Screwed terminal
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9010
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No
Frequency:	50 Hz
Device width:	71 mm
Device height:	36 mm

## Product Card

Socket outlet, Jussi, non-earthed, 1-gang, shuttered, screw terminals



---

Device depth: 71 mm

---

Min. depth of built-in installation box: 28 mm

---