

Product Card

Socket outlet, Jussi, non-earthed, 2-gang, shuttered, screwless terminals, branching terminals



Socket outlet

Socket outlet, Jussi, non-earthed, 2-gang, shuttered, screwless terminals, branching terminals



Type: 302UC

Product ID: 2TKA000955G1

GTIN: 6418677335808



There are terminals for each contact of the socket outlet and 2 X-terminals. The terminals are for max 2 rigid wires.

Technical specification

Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

Classification

Suitable for degree of protection (IP):	IP20
---	------

Packing

Package:	10/100
Unit:	PCS

ETIM Data

Number of active pins (round):	2
--------------------------------	---

Product Card

Socket outlet, Jussi, non-earthed, 2-gang, shuttered, screwless terminals, branching terminals



With signal lamp:	No
Number of units:	2
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9010
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No
Frequency:	50 Hz

Product Card

Socket outlet, Jussi, non-earthed, 2-gang, shuttered, screwless terminals, branching terminals



Device width:	71 mm
Device height:	40 mm
Device depth:	87 mm
Min. depth of built-in installation box:	17 mm