

---

# Signal Push Button

## Signal Push Button with Stereo Plug Terminal

---

**Type:** FAP3011**Product ID:** 2TKA002103G1**GTIN:** 6410070607285

Signal Push Button with LED. Additional plug for 6.3 mm Jack connector. Addressed / non-addressed function available. Good marking possibilities. Operating voltage: 9,5-28 Vac / 9,5-35 Vdc. Current consumption: 20 mA ac / 10 mA dc. Switching voltage / -current / -power: 30 Vac/35 Vdc / 100 mA ac/dc / 3 VA/W.

## Technical specification

### Classification

Enclosure class:	IP20
------------------	------

### Dimensions

Dimensions:	71x71x39 mm
-------------	-------------

Weight:	36 g
---------	------

### Thermal conditions

Operating temperature:	5 ... 40 °C
------------------------	-------------

Storage temperature:	-40 ... 70 °C
----------------------	---------------

# Product Card

Signal Push Button with Stereo Plug Terminal



## Signal products

Connector:	6,3 mm Jack
Operating voltage of signal lamp:	9,5 - 28 V ac / 9,5 - 35 V dc
Current drain of signal lamp:	20 mA ac / 10 mA dc

## Packing

Package:	1/10/100/1200
Unit:	PCS

## ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002247
Model:	Pull contact
Colour:	White
RAL-number (similar):	9010
Voltage type:	AC/DC
With transformer:	No
Degree of protection (IP):	IP20
Device width:	71 mm
Device height:	71 mm
Device depth:	39 mm