
Buzzer

Type: FIM1100

Product ID: 2TKA002128G1

GTIN: 6410070607612



Two audio frequencies available. Volume adjustment possible.
Operating voltage: 9,5 - 28 V ac / 9,5 - 35 V dc. Current consumption: 20 mA ac / 10 mA dc. Sound intensity / frequency: 70 dB / 250 Hz or 70 dB / 750 Hz (intensity measured at 30 cm distance).

Technical specification

Dimensions

Dimensions:	71x71x35 mm
Weight:	37 g

Classification

Enclosure class:	IP20
------------------	------

Thermal conditions

Operating temperature:	5 ... 40 °C
Storage temperature:	-40 ... 70 °C

Signal products

Sound frequency:	200 / 750 Hz
Sound intensity:	≤ 70 dB

Product Card

Buzzer



Electrical quantities

Operating voltage:	9,5 - 28 V ac / 9,5 - 35 V dc
Current consumption:	40 mA ac / 20 mA dc

Packing

Package:	1/10/100/1200
Unit:	PCS

ETIM Data

Model:	Buzzer
Colour:	White
RAL-number (similar):	9010
Voltage type:	AC/DC
With transformer:	No
Degree of protection (IP):	IP20
Device width:	71 mm
Device height:	71 mm
Device depth:	35 mm