

---

# Door Panel

Door Panel for office signal system

---

**Type:** FIO2000

**Product ID:** 2TKA002139G1

**GTIN:** 6410070606127



The Door Panel can be installed either surface or flush-mounted on top of a 1- or 2-gang mounting box. Compatible with Table Panel FIP2000. Operating voltage: 15 - 28 V ac. Current consumption: 75 mA (max).

## Technical specification

### Electrical quantities

Nominal voltage:	24 V
Operating voltage:	15 - 28 V ac
Current consumption:	75 mA ac (max 28 V ac syötöllä)

### Classification

Suitable for degree of protection (IP):	IP20
---	------

### Dimensions

Dimensions:	157x85x22 mm
Weight:	120 g

### Thermal conditions

Operating temperature:	5 ... 40 °C
Storage temperature:	-40 ... 70 °C

# Product Card

Door Panel for office signal system



## Packing

Package:	1/10
Unit:	PCS

## ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000064
Assembly arrangement:	Complete device
With light source:	Yes
Lamp type:	LED not exchangeable
With flashlight:	No
With fixed symbol/imprint:	No
With exchangeable symbol:	No
Application as button:	No
Mounting method:	Surface mounted (plaster)
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	White
RAL-number (similar):	9010
Transparent:	No
Device width:	85 mm
Device height:	22 mm
Device depth:	157 mm