

# Brick wall mount box

Brick wall mounting box

**Type:** AU3.32

**Product ID:** 2TKA130030G1

**GTIN:** 6410011523674



The device offers the AU3.2 mounting box modified with a 28 mm deep extension ring for use in walls built of bricks that have pipe ducts. No branch inlets are required at the bottom of the box - straight access makes wire laying easier. There is no need to bend the conduits. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C).

## Technical specification

### Packing

Package:	50
Unit:	PCS

### ETIM Data

Mounting method:	Flush mounted (plaster)
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Single
Provided with revolving ring:	No
Connectable:	Yes
Equipped with:	None
Diameter:	71 mm

# Product Card

Brick wall mounting box



Length:	71 mm
Width:	71 mm
Depth:	71 mm
Inner depth:	71 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Yes
Housing feed-through by break-out opening:	Yes
Housing feed-through by seal membrane:	No
Housing feed-through by nozzle:	No
Housing feed-through by step membrane:	No
For tube diameter:	20/25 mm
Pipe locking:	Yes
Pipe locking optional:	No
Inlet from the rear:	Yes
Material:	Plastic
Halogen free:	Yes
Surface protection:	Untreated
Colour:	White
Transparent cover:	No
Cover attachment:	Snapped on
Sealable:	No
With screening:	No
Air tight:	No
Clamp position fixed:	No
Luminaire hook mounting:	No
Special application:	None