

Junction box IP44

Junction box, IP44, Ø 115 mm, white

Type: AP7

Product ID: 2TKA140008G1

GTIN: 6410016125170













The round junction box AP7 (2,5 mm², 440 V) is similar to the AP9 and the AP10 and is equipped with 10 membrane cable entries (Ø 17 mm) and two in the bottom. Cables are easy to connect by simply inserting the stripped ends through the inlets. The cover is locked with two screws at distance of 78 mm. The box can be furnished with strainreliefs AS9, AS9.1 and AS9.3. Made of halogen free material (IEC/61249-2-21).

Technical specification

Classification

Enclosure class: IP44

Colors

Colour: White Colour code: RAL9003

Packing

Package: 5/50 Unit: **PCS**

ETIM Data

© ABB 2025

Business ID 0763403-0

Customer service

puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange**

Product Card

Junction box, IP44, Ø 115 mm, white



| ETIM Version: | ETIM-9.0 |
|-------------------------------|---------------|
| ETIM Class: | EC002600 |
| Equipped with: | None |
| Shape: | Round |
| Mounting method: | Universal |
| Mounting in the soil: | No |
| Mounting under water: | No |
| Inlet from the rear: | Yes |
| Length: | 41 mm |
| Width: | 115 mm |
| Depth: | 115 mm |
| Diameter: | 115 mm |
| Tackable: | No |
| Number of inlets: | 12 |
| Type of housing feed-through: | Seal membrane |
| Material: | Plastic |
| Halogen free: | Yes |
| Surface protection: | Untreated |
| Colour: | White |
| Degree of protection (IP): | IP44 |
| Cover model: | Blind cover |
| Transparent cover: | No |
| Cover attachment: | Screwed |
| Castable: | No |
| With casting compound: | No |
| Sealable: | No |
| Rated insulation voltage Ui: | 400 V |
| With screening: | No |
| Weatherproof: | Yes |
| Operating temperature: | -1560 °C |
| Explosion-tested version: | No |
| | |

© ABB 2025
Business ID 0763403-0
www.installationmaterials.com

Customer service puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange** +358 10 22 11